

Tower Light TL15

Introducing the **TL15 Tower Light**, a robust and versatile lighting solution, perfect for demanding environments. With advanced features and durable construction, it ensures reliable, bright illumination for any project.

Features and Benefits:

- Vertical mast
- Maximum height 6m
- Back steel telescopic section
- 3 adjustable stabilizers
- Manual lifting system with winch complete with auto-braking system (Electrical system optional)
- Mast rotatable to 340°
- Certified wind stability up to 80km/h
- Electrical coiled cable complete with housing
- ON/OFF switch for each of 2 lamps
- 4 flood lights 1600W LED
- Fork lift pockets
- Structure assembled on-site tow trailer, single axle
- 75 liters metal fuel tank
- More than 30 hours of running time
- 4 side lifting hooks
- Lockable doors
- Digital hour counter
- Series of alarms to protect the engine
- 13 KVA silent generating set PERKINS, 403A-15G1 diesel engine
- 3 KVA - 230 V - 16 A outlet with circuit breaker protection



G&J GROUP INC.

TL 15 Tower Light - Main Specifications

Engine Brand: Perkins

Engine Type: 403A-15G1

Type: Water-cooled diesel engine

Engine Speed: RPM 1500

Frequency: Hz 50

No. of Cylinders: 3 in line

Rated Power: KVA 13

KW: 10.4

Fuel Consumption at 75% Load: L/hr 2.8

G&J GROUP INC.

Electrical

Alternator Model: Leroy Somer TAL040 C

Circuit: Hard wired

Voltage: VAC 220/380

G&J GROUP INC.

Dimensions:

Height : Mast Lowered: Cm 250

Height : Mast Raised: Cm 800

Width: Cm 90

Wheels and Tires: Cm 55-36

Tower

Rotation: 340°

Lighting: 4 LED lamps 400 Watt = 1600 Watt

Rising Methods: Manual Rotation

Stabilizers

Design: Four-point design

Placement: Two rear, two front and back